

**EN 1092-1; Type 05 - PN10**
**maattabel blindflenzen**

DN	D		K		L	Bouten		C <sub>4</sub>		G <sub>max</sub>	Gew. kg	
						aantal	M	T-e	T-b			
200	340	±3,0	295	±1,0	22	8	M20	24	+4,0 / -1,5	±1,5	190	16,5
250	395		350		22	12	M20	26			235	24,1
300	445		400		22	12	M20	26			285	30,8
350	505		460		22	16	M20	26			330	39,6
400	565		515		26	16	M24	26			380	49,4
450	615		565		26	20	M24	28			425	63,0
500	670	±5,0	620	±1,5	26	20	M24	28	+7,0 / -2,0	±2,0	475	75,2
600	780		725		30	20	M27	34			575	124
700	895		840		30	24	M27	38			670	183
800	1015		950		33	24	M30	48			770	297
900	1115		1050		33	28	M30	50			860	374
1000	1230		1160		36	28	M33	54			960	492
1200	1455		1380		39	32	M36	66			1160	842

**EN 1092-1; Type 05 - PN16**
**maattabel blindflenzen**

DN	D		K		L	Bouten		C <sub>4</sub>		G <sub>max</sub>	Gew. kg	
						aantal	M	T-e	T-b			
50	165	±2,0	125	±1,0	18	4	M16	18	+2,0 / -1,3	+1,0 / -1,3	-	2,88
65	185		145		18	8	M16	18			55	3,51
80	200		160		18	8	M16	20			70	4,61
100	220		180		18	8	M16	20			90	5,65
125	250		210		18	8	M16	22			115	8,13
150	285		240		22	8	M20	22			140	10,5
200	340	±3,0	295	±1,5	22	12	M20	24	+4,0 / -1,5	±1,5	190	16,2
250	405		355		26	12	M24	26			235	25,0
300	460		410		26	12	M24	28			285	35,1
350	520		470		26	16	M24	30			330	48,0
400	580		525		30	16	M27	32			380	63,5
450	640		585		30	20	M27	40			425	96,6
500	715		650		33	20	M30	44			475	133
600	840		770		36	20	M33	54			575	226
700	910	840	36	24	M33	58	670	285				
800	1025	±5,0	950	±1,5	39	24	M36	62	+7,0 / -2,0	±2,0	770	388
900	1125		1050		39	28	M36	64			860	483
1000	1255		1170		42	28	M39	68			960	640