



FF

| DN | Gewicht | Bouwlengte | Verstelbaarheid | s | Aantal gaten | Grootste |
|------|---------|----------------------|-----------------|-----|--------------|----------|
| | ca. kg | in middenstelling | $\pm X$ | | | Diameter |
| | | mm | mm | mm | | D |
| | | | | | | mm |
| 40 | 9 | 180 | 25 | 280 | 4 | 150 |
| 50 | 11 | 180 | 25 | 280 | 4 | 165 |
| 65 | 13 | 180 | 25 | 280 | 4 | 185 |
| 80 | 17 | 200 | 25 | 310 | 8 | 200 |
| 100 | 21 | 200 | 25 | 310 | 8 | 220 |
| 125 | 26 | 200 | 25 | 310 | 8 | 250 |
| 150 | 35 | 200 | 25 | 320 | 8 | 285 |
| 175 | 45 | 220 | 25 | 340 | 8 | 315 |
| 200 | 49 | 220 | 25 | 340 | 8 | 340 |
| 250 | 64 | 220 | 25 | 360 | 12 | 395 |
| 300 | 73 | 220 | 25 | 360 | 12 | 445 |
| 350 | 96 | 230 | 25 | 360 | 16 | 505 |
| 400 | 124 | 230 | 25 | 370 | 16 | 565 |
| 450 | 141 | 250 | 25 | 390 | 20 | 630 |
| 500 | 160 | 260 | 25 | 390 | 20 | 670 |
| 550 | 194 | 260 | 25 | 410 | 20 | 740 |
| 600 | 207 | 260 | 25 | 410 | 20 | 780 |
| 650 | 238 | 260 | 25 | 410 | 24 | 840 |
| 700 | 259 | 260 | 25 | 410 | 24 | 895 |
| 800 | 354 | 290 | 25 | 460 | 24 | 1015 |
| 900 | 407 | 290 | 25 | 460 | 28 | 1115 |
| 1000 | 488 | 290 | 25 | 480 | 28 | 1230 |
| 1100 | 589 | 300 | 25 | 480 | 32 | 1345 |
| 1200 | 748 | 320 | 25 | 520 | 32 | 1455 |
| 1400 | 1037 | 360 | 25 | 560 | 36 | 1675 |
| 1600 | 1525 | 390 | 25 | 600 | 40 | 1915 |
| 1800 | 2792 | 420 | 25 | 650 | 44 | 2115 |